Seat Belt for Forklift

Forklift Seat Belt - Described in the Regulation guidelines are the application of seatbelts and operator restraints on lift trucks. It says that the liability falls on the employers' to be able to make certain that each and every machine, piece of equipment and tool is used correctly used according to the directions of the producer.

Rough Terrain forklifts need to meet the regulations of ANSI Standard ASME B56.6-1992 regarding their maintenance, inspection, fabrication, use and design.

Mobile equipment such as side boom tractors along with a Rollover Protective Structure (ROPS), have to include seat belts that meet the Society of Automotive Engineers safety requirements; Society of Automotive Engineers Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If any mobile machinery has seat belts required by law, the operator and subsequent passengers must make sure they make use of the belts whenever the vehicle is in motion or engaged in operation for the reason that this could cause the equipment to become unsteady and thus, unsafe.

When a seat belt or different driver restraint is required on a lift truck.

The seat belt requirements while operating a forklift depend on different factors. Whether or not the lift truck is equipped together with a Rollover Protective Structure, the kind of forklift itself and the year the forklift was manufactured all add to this determination. The manufacturer's directions and the requirements of the applicable standard are referenced in the Regulation.

With regards to powered industrial forklifts, ANSI Standard ASME B56.1-1993 refers to a driver restraint device, system, or enclosure. An operator restraint device, enclosure or system is designed to help the operator in lessening the chance of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The restraint device or system might comprise a seat belt, although a seat belt is not essentially a part of such machine or system.